

# SMART THUMP ST16

## Portable Cable Fault Location System



- Delivers 1500 J at 8/16 kV
- 16-kV DC high voltage proof test and insulation resistance test
- Easy Go automatic test sequence to proof test, prelocate and pinpoint
- Interprets test results for user
- 5.7 in. transfective color display
- Safety / grounding check
- USB interface

### DESCRIPTION

The SMART THUMP ST16 Portable Cable Fault Locating System provides safe, efficient and extremely easy-to-use solutions for quickly identifying, prelocating and pinpointing various types of cable faults for power cables. The ST16 was developed to meet the requirements for typical low- and medium-voltage distribution cable fault location markets.

Circuit parameters include:

- System voltage up to 35 kV
- Insulation EPR or XLPE
- Typical conductor sizes between #2 and 500 MCM (34 mm<sup>2</sup> to 250 mm<sup>2</sup>)
- Typical circuit lengths from a few hundred feet (100 m) up to 3 miles (17,000 ft or 5,000 m)

Typical end users include: operations department of power utility companies, electrical departments within municipalities including street light maintenance, private network operators, high voltage electrical contractors, service companies, port authorities, mining, airports, military bases, petrochemical and paper companies.

The ST16 unit incorporates HDW's "E-Tray" technology, a concept that has been already proven in other products (EZ-Thump, EZ-Restore Overdrive, and TDR T3090) and which will be carried forward into new Megger products in the future. The E-Tray adds the unique capability to access and operate every function through an innovative and intuitive user interface, without the need to make adjustments and the software suggesting the next logical step.

### APPLICATIONS

The SMART THUMP ST16 represents a new generation of advanced underground cable fault locating systems that require less training than a traditional thumper-only system. It is the only fault locator with built-in intelligence to interpret the results of the initial test sequence. The "turn & click" rotary button operation lets the user automatically proof test, pre-locate, and pinpoint the fault from one convenient control console. No adjustments are required. The unit automatically sets the thump voltage to minimize the stress applied to the cable. The ST16 features an automatic safety check to protect the user from incorrect or faulty ground connections (F-Ohm).

The heavy-duty wheels of the unit are ideal for use in rough terrain. The ST16 is capable of being permanently installed in a vehicle (truck mount version).

### FEATURES AND BENEFITS

This fully integrated system can be operated from either its internal battery/inverter, external 12 VDC or 120/230 VAC. Additional features are:

- "Quick-Steps" is especially convenient where operators may not be called upon to use the equipment on a regular basis
- "Expert Mode" provides up to 20 individual TDR features to the experienced user for optimum fault locating results
- Custom configurable menus for the TDR function
- DC testing up to 16 kV with indication of insulation resistance value
- Rugged, powder coated IP54 designed enclosure
- Safe Op check protects user from incorrect and/or faulty ground connections (F-Ohm)
- Easy Go operation eliminates lengthy training
- Quick access to all components in case of service

**SPECIFICATIONS**

**Impulse Generator (Thumper)**

**Operating modes:**

Arc Reflection Method (ARM®)	0-8/0-16 kV
ICE surge pulse (optional in North America), standard other countries	0-8/0-16 kV
Direct surge (Thumping)	0-8/0-16 kV
DC-HV proof test and resistance readout (Ω)	0-8/0-16 kV
Burning / Fault Conditioning	0-8/0-16 kV
Sheath fault test & pinpointing / Secondary Fault Locating (optional)	0-5/10 kV

**TDR**

TDR mode and all prelocation functions (25,000 ft, optional 100,000 ft)

**Energy Output**

Dual stage: 1500 J @ 8 kV and 16 kV  
Proof test: 0 to 16 kV continuous  
Burn current: 60 mA max

**Key Features**

Single-shot thump in ARM  
Built-in inductive type ARM filter  
8 second thump cycle @ max output  
Automatic cable and system discharging

**Display Features**

Transflective TFT color display, sunlight proof  
5.7 in., 640 x 470 pixel resolution

**Power Options**

120/230 V, 60/50 Hz ac operation  
12 V deep cycle marine battery with internal dc charger/inverter (standard)

**SMART Features**

Entirely automatic test sequences includes proof test, prelocate, and pinpoint  
Automatic interpretation regarding type of fault (i.e. open, burnt in the clear, short)  
Automatic adjustment of thump voltage (uses selectable)  
Automatic alphanumeric display of cable and fault distance

**USB**

Host interface 2.0  
TDR trace export and system upgrades

**Mounting and Enclosure**

Mounted on heavy-duty wheels (14")  
Rain tight powder coated enclosure IP54 (open)  
(Also available as vehicle-mount unit)

**Digital "Analog" Meter**

Displayed on LCD screen

**Environmental**

Operating Temperature: -20C to +50C; -4F to +122F  
Storage Temperature: -25C to +65C; -13F to +149F

**IP Rating**

IP54 (with top open)

**Weight**

318 lbs (134 kg) includes wheels, battery and inverter & 50 ft of HV / Ground Cable

**Dimensions**

20 x 46 x 24 in. (500 x 1170 x 600 mm) W x H x D

**Optional Accessories , see next page for ordering information**



1 - Elbow adapter 25 kV	865000200100000	10 - Vise grip with nutted stud	210.VG7R
2 - Elbow adapter 15 kV	865000100100000	11 - Vise grip with 14 mm female MC	210.VG7MC
3 - Elbow adapter 35 kV (Cooper/Purple)	865000300100000	12 - Vise clamp brass	210.0407 or
4 - Elbow adapter 35 kV (Elastimold)	865000300200000		210.0407MC (w/female MC)
5 - Female MC 10 mm with rubber boot	210.MC KB10AR	13 - Vise clamp brass on mounting plate	210.0406G
6 - Male MC 14 mm with rubber boot	210.MC KST 14AR	14 - Bushing pin connector 15/25 kV with 14 mm female MC	86600020050000B
7 - Female MC 14 mm with rubber boot	210.MC KBT 14AR	15 - Narrow hot line clamp with 14 mm female MC	210.MCLA820
8 - HD battery clamp with 10 mm male MC	210.810001055	16 - Hotline clamp	210.S1530
9 - HD battery clamp with 10 mm male MC	210.820003130	17 - Small hotline clamp	210.S1520

\*For other configurations of termination please contact factory

## ORDERING INFORMATION

	MOUNT	REMOTE CONTROL	POWER	ST16	MODEL				Text
					WW	XX	YY	Z	
SELECT MOUNTING OPTION	CART	NO	AC / Battery / EXT DC	Cart mounted Unit, Standard ,3 Power Options: AC120/230V 50/60Hz, Internal Battery 12V, External 12VDC	M1				
	TRUCK	NO	AC / EXT DC	Truck Mount Unit AC only / ext. DC option	M2				
	TRUCK	NO	AC ONLY	Truck Mount Unit AC only	M3				
	CART	NO	AC ONLY	Cart mounted Unit AC Only	M4				
	TRUCK	YES	AC ONLY	Truck Mount Unit AC Only / remote control	M5				
	TRUCK	YES	AC / EXT DC	Truck Mount Unit AC Only / remote control / ext. DC option	M6				
SELECT CABLE LENGTH				12 ft Custom Cable		12			
				25 ft Custom Cable		25			
				50 ft Standard Cable		50			
SELECT CABLE TERMINATION				14 mm Male MC with Hotline Clamps (North America)			T1		
				14 mm Male MC with Vise Grips (North America)			T2		
				Hardwired to Battery Clamps on HV & "G" Clamp to Ground (No MC Connectors)			T3		
				10 mm Female MC with Battery Clamps (excluding North America)			T4		
SELECT SOFTWARE OPTION (Selection of software option can be any combination)				ICE (Surge Pulse)				I	
				Sheath fault testing / Secondary Fault Locating				H	
				Sectionalizing Software				S	
				Manual voltage Selection				M	

Item	Cat No.	Item	Cat No.
<b>Included Accessories</b>			
6 ft (1.8 m) mains supply lead set (US/SCHUKO/UK)	1002-889	<b>Cable racks and reels - terminations typical in markets outside North America and Mexico **</b>	
Instruction manual	AVTMST16	C401 Cable rack system, HV 50kV, 230Vac mains, GND cable, 125 ft each	1003-916
<b>Optional Accessories</b>		C403 Cable rack system, HV 50kV, GND cable, 125 ft each	1003-917
15-kV elbow 14 mm female MC connector	865000100100000	C403HT Cable rack system, HV 50kV, GND cable, 125 ft each, mounted on 15" wheel hand cart	1003-918
25-kV elbow 14 mm female MC connector	865000200100000	C403-150 Cable rack system, HV 50kV, GND cable, 150 ft each	1003-919
35-kV Elbow 14 mm female MC connector	865000300100000	C403P Set of 2 individual hand reels (HV and GND), 125 ft each	1003-920
Digiphone Plus surge wave receiver	871500500100000	<b>** Standard terminations on cable reels in markets outside North America and Mexico:</b>	
ESG NT digital earth fault locator	871500200200000	HV output cable: 10mm female MC, w/ battery clamp HV Return (far end): 10 mm female MC, w/ battery clamp Cable reel HV input: 10mm male MC HV Return: 10 mm male MC	
<b>Cable racks and reels - terminations typical in North America and Mexico *</b>			
C401 Cable rack system, HV 50kV, 115Vac mains, GND cable, 125 ft each	864000100100000		
C403 Cable rack system, HV 50kV, GND cable, 125 ft each	864000200100000		
C403HT Cable rack system, HV 50kV, GND cable, 125 ft each, mounted on 15" wheel hand cart	864000200200000		
C403-150 Cable rack system, HV 50kV, GND cable, 150 ft each	864000200300000		
C403P Set of 2 individual hand reels (HV & GND), 125 ft each	864002002500000		
* Standard North America and Mexico terminations on cable reels: HV output cable: 14mm male MC , Cable reel HV input: 14mm female MC HV Return: Open spade lug (hook)			

**SALES OFFICE**  
 4271 Bronze Way  
 Dallas, TX 75237-1019 USA  
 T 1 800 723 2861 (USA only)  
 T +1 214 333 3201  
 F +1 214 331 7399

**ST16\_DS\_EN\_V05**  
 www.megger.com  
 ISO 9001  
 The word 'Megger' is a registered trademark



USsales@megger.com